

Attorney Docket: 1934/50364
PATENT



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: RUSSELL TAYLOR ET AL.

Serial No.: NOT YET ASSIGNED

Filed: OCTOBER 1, 2001

Title: AUTOMATED TESTING OF HYBRID ACTUATOR

CLAIM FOR PRIORITY UNDER 35 U.S.C. §119

Box PATENT APPLICATION
Commissioner for Patents
Washington, D.C. 20231

October 1, 2001

Sir:

The benefit of the filing date of prior foreign application No. 00308595.8, filed in the European Patent Office on 29 September 29, 2000, is hereby requested and the right of priority under 35 U.S.C. §119 is hereby claimed.

In support of this claim, filed herewith is a certified copy of the original foreign application.

Respectfully submitted,

Gary R. Edwards
Registration No. 31,824

CROWELL & MORING, LLP
Intellectual Property Group
P.O. Box 14300
Washington, DC 20044-4300
Telephone No.: (202) 624-2500
Facsimile No.: (202) 628-8844
GRE:kms
(CAM 37256.005)

THIS PAGE BLANK (USPTO)

**Europäisches
Patentamt****European
Patent Office****Office européen
des brevets**jc997 U.S. PTO
09/966744
10/01/01**Bescheinigung****Certificate****Attestation**

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

00308595.8

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

I.L.C. HATTEN-HECKMAN

THIS PAGE BLANK (USPTO)



Anmeldung Nr:
Application no.: 00308595.8
Demande no:

Anmeldetag:
Date of filing: 29.09.00
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

SIEMENS AKTIENGESELLSCHAFT
Wittelsbacherplatz 2
80333 München
ALLEMAGNE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

Automated testing of hybrid actuator

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)
revendiquée(s)

Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

/00.00.00/

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

H02P/

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

THIS PAGE BLANK (USPTO)

AUTOMATED TESTING OF HYBRID ACTUATOR

The present invention relates to an apparatus and a method for automated testing of a hybrid actuator. The term hybrid actuator relates to
5 a combined indicator lens and potentiometer actuator as disclosed in a co-pending European Patent Application No.... our file number 2000P05003/EP entitled "Hybrid Actuator" and filed concurrently herewith. In particular, the invention relates to the automated testing of a hybrid actuator disposed in a frequency inverter supplying a variable speed
10 motor, for example a COMBIMASTER [Registered Trademark] 411 combination motor and inverter.

Variable speed motors are used in many settings, for example for driving mechanical handling equipment, for driving electric fans or for powering conveyor belts. Rather than simply varying the voltage applied
15 to a motor, it has been found more efficient to use frequency inverters to convert mains electricity into a variable, three phase power supply.

Variation of the speed of operation of variable speed motor can be achieved through the rotation of an external knob which engages an internal potentiometer. It is often advantageous that adjustment of the
20 speed of operation be as simple as possible and as a result the knob can be arranged to be operable by hand or by means of a coin or a screwdriver. The rotational adjustment may also be imparted by means of a dedicated tool.

The inverter can be in a number of different operational states, for
25 example normal operation, malfunction and test mode. To indicate the current state, the inverter may be provided with an indicator arrangement. This indicator arrangement may comprise internal indicator lamps, for

example light emitting diodes (LEDs), and corresponding indicator ports in a wall of the inverter housing. The provision of an indicator arrangement reduces the need for internal access for inspection and is thus a practical safety feature.

5 The indicator lamps can be arranged to blink with different patterns corresponding to different operational states. Alternatively indicators may be provided which can generate signals of a variety of colours, for example red for malfunction, green for normal operation. It is possible that a single indicator can produce signals of more than one colour, for example certain
10 light emitting diodes allow the production of light at a number of different wavelengths. Naturally other signals can be used to indicate operational states for example audible signals from a loudspeaker.

 Of great importance in the reliable operation of electrical devices, inverters included, is isolation from undesirable material. Dust and water
15 can cause particular problems and standards have evolved which detail the degree to which a device is proof against the ingress of water and dust. The environmental protection achieved by frequency inverters is graded along an index of protection (IP) wherein the protection against dust is graded along one scale and against water on another scale, for example an
20 IP rating IP56 corresponds to 5 on the dust scale (ranging from no protection - 0 to total protection - 6) and 6 on the water scale (ranging from no protection - 0 to protection against continuous submersion - 8).

 For each indicator port and potentiometer adjustment knob port in an inverter's housing the index of protection for the whole inverter is
25 marginally more compromised. If the number of possible ingress points can be reduced a higher IP rating can be attained. In the co-pending European Patent Application No. ... discussed above (Attorney Docket Number 2000P05003/EP), there is disclosed an inverter having a single

ingress point for a hybrid actuator. The hybrid actuator can be rotated to impart an adjustment upon a potentiometer. Furthermore the hybrid actuator is made of a transparent material to allow the light from an internal indicator lamp to be visible through the single ingress point.

5 The hybrid actuator can be tested manually by turning the actuator to a number of predetermined positions and confirming that the inverter performs satisfactorily. The manual test then requires that the indicator arrangement be inspected to ensure that the various possible states of the inverter are correctly displayed through the lensing function of the hybrid
10 actuator. Finally the manual test must ensure that the hybrid actuator is returned to a minimum potentiometer setting to avoid damage when the inverter is first used.

Manual testing is performed by a production operative. The production operative often has many other tasks apart from testing. The
15 drawbacks of manual testing thus include: human error; inconsistent testing criteria; added time overheads (for both the production operative performing the test and for the additional time the inverter is in production); and interruption of other non-testing tasks.

In accordance with one aspect of the present invention, there is
20 provided a testing apparatus for testing an electrical device comprising: a housing; a rotatable control means; an indicator arrangement; and a hybrid actuator, the hybrid actuator being substantially transparent to allow light from the indicator arrangement to be observed from outside the housing, engaging with the rotatable control means and rotating about an axis;
25 characterised in that the test apparatus includes: a rotatable test head which has an engaging portion for engaging a head portion of said hybrid actuator; a light sensing means; a processing means for receiving sensed light data from the light sensing means, for receiving performance data

from the electrical device and for controlling the movement of the rotatable test head; and a drive means for driving the rotatable test head about the axis in accordance with a control signal generated by the processing means.

It is preferred that the light sensing means is provided upon the
5 rotatable test head.

It is noted that a light sensing means may be provided either on the rotatable test head or close enough to the rotatable test head to be able to monitor light emitted by the hybrid actuator. In one possible arrangement the light sensing means may be provided behind the rotatable test head and
10 the rotatable test head may be substantially transparent thereby allowing light to penetrate through to the light sensing means. In another possible arrangement, the light sensing means is disposed in a non-rotating axial portion of the rotatable test head and a remaining radial portion of the rotatable test head rotates about the axial portion.

15 Preferably, the engaging portion of the rotatable test head engages with a corresponding receiving recess provided on the head portion and thereby aligns the light sensing means with the hybrid actuator.

The light sensing means advantageously monitors light emitted by the indicator arrangement.

20 In a preferred embodiment, the electrical device is an inverter, the rotatable control means is a potentiometer and the indicator arrangement is a light emitting diode. Here the performance data received from the inverter may be a sample of the output voltage of the inverter.

Automated testing of the hybrid actuator gives a great improvement
25 over manual testing since a high level of quality can be maintained with the minimum of additional testing time and production operative attention.

In a further aspect of the present invention there is provided a method for testing an electrical device an electrical device comprising: a

housing; a rotatable control means; an indicator arrangement; and a hybrid actuator, the hybrid actuator being substantially transparent to allow light from the indicator arrangement to be observed from outside the housing, engaging with the rotatable control means and rotating about an axis; the

5 method characterised by the steps of: providing a test apparatus which includes: a rotatable test head; a light sensing means; a drive means; and a processing means for controlling the movement of the rotatable test head; engaging the rotatable test head with a head portion of the hybrid actuator; driving the rotatable test head about the axis into a plurality of different

10 testing positions in accordance with a control signal generated by the processing means; in each of the different testing positions, monitoring performance data for the electrical device; monitoring the light emanating from the hybrid actuator, the light sensing means sensing the light emanating from the hybrid actuator and generating sensed light data; and

15 receiving and processing the sensed light data and the performance data and generating a report of the received data.

For a better understanding of the present invention, reference will now be made, by way of example only, to the accompanying drawings in which:-

20 Figure 1 shows a hybrid actuator as described in the co-pending European Patent Application No. ... discussed above (Attorney Docket Number 2000P05003/EP);

Figure 2 shows an apparatus according to the present invention for testing inverters having hybrid actuators as shown in Figure 1; and

25 Figure 3 shows a schematic diagram of the apparatus of Figure 2.

Prior art inverters have independent potentiometer knobs and indicator ports. However independent potentiometer knobs and indicator ports inevitably require a corresponding number of independent access

ports. The more access ports the more difficult it is to maintain a high IP rating.

Figure 1 illustrates a portion of an inverter as described in the co-pending European Patent Application No. ... discussed above (Attorney
5 Docket Number 2000P05003/EP). The inverter has a housing 130 within which are arranged a hybrid actuator 100, a light emitting diode 110 and a potentiometer 120. The hybrid actuator 100 has a head portion 114 outside the inverter housing 130 and a shaft portion 108 within the housing 130.

10 A tip 112 of the shaft portion 108 is arranged to be adjacent to the LED 110 with a small gap 124 therebetween. In further embodiments of the hybrid actuator 100, the small gap 124 may be absent. The hybrid actuator 100 is made of a substantially transparent material, for example plastic or toughened glass, and thus light emitted by the LED 110 is
15 conveyed from the LED 110 to the outside of the inverter via a "light tube" defined by the shaft portion 108 and the head portion 114 of the hybrid actuator 100. To facilitate efficient passage of light through the shaft portion 108, the surfaces of the shaft portion 108 are made reflective whilst the outer surface of the head portion 114 is roughened to disperse any light
20 originating within the inverter housing 130.

The end of the shaft portion 108 is provided with an engaging surface 122, for engaging with a corresponding receiving portion 126 of the potentiometer 120. When the head portion 114 of the hybrid actuator 100 is rotated from outside the inverter housing 130, the rotational moment thus
25 acts upon the potentiometer 120 and the speed of the motor is adjusted accordingly. It will be understood that the engaging surface 122 and the corresponding receiving portion 126 may take a variety of known forms from a simple key and key-hole arrangement to an arrangement where the

engaging surface 122 and the receiving portion 126 are both provided with interlocking fingers or hooks.

The head portion 114 of the hybrid actuator 100 is provided with an adjustment slot 102 and a wiper 116. The adjustment slot 102 is arranged
5 to allow an adjustment tool, for instance a coin, a screwdriver or a dedicated, automated rotating test head, to be inserted therein and thereby cause the hybrid actuator to rotate.

To complete an environmental seal between the inside 132 and the outside 134 of the inverter housing 130, a sealing O-ring 104 is provided.
10 The sealing O-ring 104 prevents the ingress of water and or dust particles even when the hybrid actuator 100 is rotated and is disposed within a port hole 128 in the inverter housing 130. A further retaining O-ring 106 is disposed at the inner rim of the port hole 128 and serves to retain the hybrid actuator 100 in axial position as well as supplementing the sealing function
15 of the sealing O-ring 104.

Figure 2 illustrates the relation between the hybrid actuator 100 and a testing apparatus 200. The testing apparatus 200 comprises a rotatable test head 204, processing means 208 and drive means 206. The drive means 206 applies a torque which drives the rotatable test head 204 in accordance
20 with a control signal 212 generated by the processing means 208. The processing means 208 may be a general purpose computer carrying out a set of programmed test instructions and relaying corresponding control signals to the drive means 206. Alternatively the processing means 208 may be a component of an application specific integrated circuit having
25 storage means (not shown) and the processing means 208 operates in accordance with instructions stored on the storage means.

It will be understood that the testing apparatus 200 must derive energy from a power supply. Examples of possible power supplies include mains electricity and battery power (not shown).

5 The hybrid actuator 100 and the rotatable test head 204 both rotate about an axis 220. The rotatable test head 204 is provided with an engaging portion 202 and a light sensing means 210. The engaging portion 202 engages with the adjustment slot 102 on the hybrid actuator 100 thereby allowing the testing apparatus 200 to impart a rotation to the potentiometer 120 by means of the rotatable test head 204 and the hybrid
10 actuator 100.

The light sensing means 210, for example a charged coupled detector or a photoresistor, is used to check the light emanating from an indicator arrangement, for example the LED 110, for brightness, colour and functionality. Not only must the light emanating from the hybrid actuator
15 100 be visible, the pattern of indications generated by the light, for example sequences of short and long flashes or blinking, must be consistent with the operational state of the inverter as a whole. When the indicator arrangement generates light of different wavelengths, the light sensing means 210 can be arranged to distinguish between the different
20 wavelengths.

Light sensing means 210 may comprise a photocell. However, it will be appreciated that other light sensing means may be employed.

The engaging portion 202 of the rotatable test head 204 is rotatable throughout a range of positions corresponding to permitted potentiometer
25 settings. At the end of each test session the rotatable test head 204 returns the potentiometer 120 to the lowest setting to prevent damage upon first usage.

The testing of the operation of the potentiometer 120 and of the indicator arrangement 110 can thus be performed through testing of the hybrid actuator 100 as it operates as a potentiometer knob and as an indicator lens respectively. Furthermore the testing of the hybrid actuator
5 100 can be automated.

Figure 3 illustrates the apparatus of Figure 2 in a more schematic form. The processing means 208 receives inverter performance data 304 and sensed light data 306 from an inverter performance sensing means 302 and the light sensing means 210 respectively. Examples of inverter
10 performance sensing means 302 include a voltmeter which monitors the output voltage signal generated by the inverter, an ammeter which monitors the output current produced by the inverter, and a frequency meter for monitoring the output frequency produced by the inverter.

Control signals 212 are generated by the processing means 208 in
15 accordance with a set of instructions and transmitted to the drive means 206. Advantageously, the processing means 208 may be arranged to monitor the performance of the drive means 206.

It will be understood that the processing means 208 will be associated with a variety of conventional peripheral devices. Information,
20 for instance the testing program, may be stored and retrieved by the processing means 208 from a storage means 320. Conventional storage means include hard disks, read only memory and random access memory. Further input can be directed to the processing means 208 by means of an input device 330, for example a keypad or a light pen. Similarly the
25 processing means 208 can be arranged to generate a report by means of an output device 310, for example a printer, a display or a loudspeaker.

THIS PAGE BLANK (USPTO)

CLAIMS:

1. A testing apparatus (200) for testing an electrical device comprising: a housing (130); a rotatable control means (120); an indicator arrangement (110); and a hybrid actuator (100), the hybrid actuator (100) being substantially transparent to allow light from the indicator arrangement (110) to be observed from outside the housing (130), engaging with the rotatable control means (120) and rotating about an axis (220);

characterised in that the test apparatus (200) includes:

a rotatable test head (204), which has an engaging portion (202) for engaging a head portion (114) of said hybrid actuator (100);

a light sensing means (210);

a processing means (208) for receiving sensed light data from the light sensing means (210), for receiving performance data from the electrical device and for controlling the movement of the rotatable test head (204); and

a drive means (206) for driving the rotatable test head (204) about the axis (220) in accordance with a control signal (212) generated by the processing means (208).

2. A testing apparatus according to Claim 1, wherein the light sensing means (210) is provided upon the rotatable test head (406).

3. A testing apparatus according to Claim 2, wherein the engaging portion (202) of the rotatable test head (204) engages with a corresponding receiving recess (102) provided on the head portion (114) and thereby aligns the light sensing means (210) with the hybrid actuator (100).

4. A testing apparatus according to Claims 1, 2 or 3, wherein the light sensing means (210) monitors light emitted by the indicator arrangement (110).
5. A testing apparatus according to any one of Claims 1 to 4, wherein the electrical device is an inverter, the rotatable control means (120) is a potentiometer and the indicator arrangement (110) is a light emitting diode.
6. A testing apparatus according to Claim 5, wherein the performance data received from the inverter is a sample of the output voltage of the inverter.
7. A method for testing an electrical device comprising: a housing (130); a rotatable control means (120); an indicator arrangement (110); and a hybrid actuator (100), the hybrid actuator (100) being substantially transparent to allow light from the indicator arrangement (110) to be observed from outside the housing (130), engaging with the rotatable control means (120) and rotating about an axis (220); the method characterised by the steps of:
- providing a test apparatus which includes: a rotatable test head (204); a light sensing means (210); a drive means (206); and a processing means (208) for controlling the movement of the rotatable test head (204);
 - engaging the rotatable test head (204) with a head portion (114) of the hybrid actuator (100);
 - driving the rotatable test head (204) about the axis (220) into a plurality of different testing positions in accordance with a control signal (212) generated by the processing means (208);

in each of the different testing positions, monitoring performance data (304) for the electrical device;

monitoring the light emanating from the hybrid actuator (100), the light sensing means (210) sensing the light emanating from the hybrid actuator (100) and generating sensed light data (306); and

receiving and processing the sensed light data (306) and the performance data (304) and generating a report of the received data.

THIS PAGE BLANK (USPTO)


ABSTRACT**AUTOMATED TESTING OF HYBRID ACTUATOR**

There is provided a testing apparatus (200) for a hybrid indicator lens and potentiometer actuator (100). The hybrid actuator (100) serves both as a knob for a potentiometer (120) and as a lens to convey light from an indicator arrangement (110). The test apparatus (200) includes a rotatable test head (204) having a light sensing means (210) and an engaging portion (202). The engaging portion (202) engages with a corresponding receiving recess (102) provided on a head portion (114) of said hybrid actuator (100) and thereby aligns the light sensing means (210) with the hybrid actuator (100). The testing apparatus (200) performs automated tests which include rotation of the hybrid actuator (100), and therefore the potentiometer (120) to a range of test settings and inspection of the functionality of the indicator lens arrangement (110).


[Figure 2]

THIS PAGE BLANK (USPTO)

1/3



4/2






Fig 3.

THIS PAGE BLANK (USPTO)